## SAFETY DATA SHEET



1. Identification

**Product identifier Rapid Set Cement** 

Other means of identification

Product code 101002000, 101010050, 101010088, 101012000, 101013000

Recommended use Industrial use. None known. Recommended restrictions Manufacturer/Importer/Supplier/Distributor information

CTS Cement Manufacturing Corporation Company name

12442 Knott Street Garden Address

> Grove, CA 92841 **United States**

Telephone 1-800-929-3030 E-mail info@ctscement.com

Safety Officer **Contact person** 

**Emergency telephone** 1-800-929-3030 (8 AM - 5 PM)

number

2. Hazard(s) identification

Physical hazards

Not classified. **Health Hazards** 

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 1 Carcinogenicity Category 1A

Specific Target Organ Toxicity, Single

Exposure

Specific Target Organ Toxicity,

Repeated Exposure **OSHA** defined hazards

Not classified. Label elements



Signal word Danger

**Hazard statement** Causes skin irritation. Causes serious eye damage.

**Precautionary statement** 

Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Prevention

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation

Category 3 respiratory tract irritation

Category 2 (Lungs)

occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Storage Store in dry location. Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. Disposal

Hazard(s) not otherwise None known.

classified (HNOC)

## 3. Composition/information on ingredients

## **Mixtures**

Chemical n
------------

Calcium Sulfoaluminate	CAS number	%
Cement	960375-09-1	90-100
Silica (Quartz) Crystalline	14808-60-7	<0.1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by **Composition comments** volume.

Rapid Set Cement SDS US

#### 4. First-aid measures

If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if Inhalation

symptoms develop or persist.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact Eye contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Immediately rinse mouth and drink plenty of water. Call an ambulance and take these instructions. Ingestion

Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Upper respiratory tract irritation. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

#### **General information**

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire. During

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Specific hazards arising from the

fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

## Specific methods General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner. Minimize dust generation and accumulation. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

## **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store in dry location. Store away from incompatible materials (see Section 10 of the SDS).

Rapid Set Cement SDS US

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form Type Value **US. ACGIH Threshold Limit Values** Form Components Type Value

US. NIOSH: Pocket Guide to Chemical Hazards

Form Components Type Value

**Biological limit values** 

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses or safety goggles unless full face respirator is in use. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding Respiratory protection

the exposure limits.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Solid. Physical state Powder. Form Color Tan. Low Odor

Not available. Odor threshold 11 - 12 when wet Not applicable. Melting point/freezing point Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable. Not applicable. **Evaporation rate** Non combustible. Flammability (solid, gas)

Rapid Set Cement SDS US Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

ı ıaııı

Not applicable.

Vapor pressure Vapor density Relative density

Not applicable. 2.98 @ 20°C

Not applicable.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Decomposition temperature Not applicable. 2460 °F (1350 °C)

Not applicable.

Other information

Viscosity

Bulk density 60 lb/ft<sup>3</sup>

Partition coefficient

(oil/water)

Not applicable.

VOC (Weight %)

0 g/l when mixed with water

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** 

Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Avoid temperatures exceeding the decomposition temperature. Contact with incompatible materials.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

Incompatible materials

**Hazardous decomposition** 

products

Sulfur oxides.

Strong oxidizing agents.

## 11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of dusts may cause respiratory irritation. Prolonged inhalation may be harmful.

**Skin contact**Causes skin irritation. Prolonged contact with wet cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

**Ingestion** Swallowing may cause gastrointestinal irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Upper respiratory tract irritation. Coughing.

Discomfort in the chest. Shortness of breath. Skin irritation.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components Species Test Results

**Skin corrosion/irritation** Causes skin irritation.

Rapid Set Cement SDS US

Serious eye damage/eye

irritation

Causes serious eye damage.

## Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization No data available.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are mutagenic

or genotoxic.

Carcinogenicity May cause cancer.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June

2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational

## IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, quartz (CAS 14808-60-7)

1 Carcinogenic to humans.

**NTP Report on Carcinogens** 

Silica, quartz (CAS 14808-60-7)

Known To Be Human Carcinogen.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity No data available.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility

that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data available.

Bioaccumulative potential Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential,

endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

No data is available on the degradability of this product.

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal

company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

Rapid Set Cement SDS US

Version #: 02 Revision date: - Issue date: 27-January-2018 5 / 7

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Rapid Set Cement SDS US

## CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard

categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US** state regulations

**US. Massachusetts RTK - Substance List** 

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania Worker and Community Right-to-Know Law

Silica, quartz (CAS 14808-60-7)

**US. Rhode Island RTK** 

Not regulated.

**US. California Proposition 65** 

Silica, quartz (CAS 14808-60-7)

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

**△ WARNING** 

CANCER and REPRODUCTIVE HARM - www.P65Warnings.ca.gov

## International Inventories

 Country(s) or region
 Inventory name
 On inventory (yes/no)\*

 United States & Puerto Rico
 Toxic Substances Control Act (TSCA) Inventory
 Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 27-January-2019

Revision date

Version # 02

HMIS® ratings Health: 3
Flammability: 0
Physical hazard: 0

Disclaimer CTS Cement Manufacturing Corporation cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the

best knowledge and experience currently available.

Rapid Set Cement SDS US

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).